Flux

Lunada Bay Tile takes a fresh look at the cherished craft of art glass with Flux hand cast glass field tiles. A revitalization of a customer favorite, the Old Fashioned glass collection has been reimagined in timeless shapes and of-the-moment hues. These luminous tiles wash surfaces in glimmering style. Flux pairs perfectly with our Origami Field dimensional glass and Contourz concrete tiles, opening design opportunities to play with elevation and coordinating hues.





Exterior

Unaffected

Unaffected

Passed

Please visit LunadaBayTile.com for our complete product offerings, applications and installation instructions.

© 2021 Lunada Bay Tile. All Rights Reserved

Interior

FLOOR APPLICATIONS

Interior Wall/Backsplash			Yes	Shower No No		No
Fireplace/Cooktop Surround			Yes *	Steam Shower No N/A		
Shower Wall			Yes	Light Residential No No		
Steam Shower			No	Residential	No	No
Exterior Wall			No			
Pool, Spa or Water Feature (fully submerged)			No			
PRODUCT SPECS				TESTING		
Size (Dimension In Nominal Size)	Coverage (Pieces Per SF)	F	Packaging (Per Box)	Standards Methods		
4 x 4	9.673	42 [Pieces/4.342 SF	Breaking Strength	ASTM C-648	>350 PSI
4" Hex	11.17	38 F	Pieces/3.402 SF	Water Absorption	ASTM C-373	Impervious < 0.05%

Suitable

(Dimension In Nominal Size)	(Pieces Per ŠF)	(Per Box)		Standards Meth
4 x 4	9.673	42 Pieces/4.342 SF	Breaking Strength	ASTM C-648
4" Hex	11.17	38 Pieces/3.402 SF	Water Absorption	ASTM C-373
4 x 8	4.788	20 Pieces/4.18 SF	Chemical Resistance	ASTM C-650
Shade Variation	Grout Joint Recommendation		Freeze/Thaw	ASTM C-1026
V1 - V2 Slight Variation	1/8" (3 mm)		Thermal Shock	ASTM C-484
				NOTEC

NOTES

Since variations are common in artistic glass tile, we recommend final selection be made from an actual tile mock-up. To achieve optimal results in shading, layout and design, tile should be randomly selected from multiple boxes during installation. We recommend a minimum of 10% overage on all orders. Please take care when grouting and protect surface from abrasion. **Installation constitutes acceptance**. We advise retaining control samples to aid in color matching if additional material is required (match not guaranteed).

MAINTENANCE

A routine cleaning of **Flux** tile can be done with a light duty non-abrasive, close to neutral pH detergent cleaner.

* Acceptable for use near open flame or heat source; However it is NOT considered 'Fire Glass'.

RECOMMENDED USAGE

Application

FLOOR APPLICATION DEFINITIONS:

Light Residential - Flooring areas subject to soft-soled footwear or normal footwear traffic without abrasive soil/dirt, such as bathrooms and bedrooms without exterior access and minimal pivot points.

Residential - Flooring areas subject to soft-soled or normal footwear traffic that may contain amounts of abrasive soil/dirt, such as living rooms, dining rooms or other rooms with exterior access.