Tomei

The Tomei glass series was built with a palette and style inspired by the great modern architects: Gehry, Hadid, and Mies van der Rohe. The meticulously curated colors and shapes provide a series of versatile design components for a multitude of spaces. Use modestly, or combine elements to create graphic appeal.



Passed

Please visit LunadaBayTile.com for our complete product offerings, applications and installation instructions.

© 2020 Lunada Bay Tile. All Rights Reserved

RECOMMENDED USAGE			FLOOR APPLICATIONS		
Application		Suitable		Interior	Exterior
Interior Wall/Backsplash		Yes	Shower	Yes *	Yes *
Fireplace/Cooktop Surround		Yes *	Steam Shower	Yes *	N/A
Shower Wall		Yes	Light Residential	Yes A	No
Steam Shower		Yes	Residential	No	No
Exterior Wall		Yes	Note: Silk finish is recommended for floor/foot traffic applications and		
Pool, Spa or Water Feature (fully submerged)		No **	usage.		
PRODUCT SPECS			TESTING		
Size (Dimension In Nominal Size)	Coverage	Packaging (Per Box)	Standards Methods		
½ x 1 Mini Brick	0.93 (SF/ Sheet)	5 Sheets/4.65 SF	Breaking Strength	ASTM C-648	>650 PSI
					I

(Dimension In Nominal Size)	Coverage	(Per Box)
½ x 1 Mini Brick	0.93 (SF/ Sheet)	5 Sheets/4.65 SF
1 x 1 Mosaic	1.10 (SF/ Sheet)	5 Sheets/5.50 SF
3 x 6	8.60 (PCs/SF)	24 Pieces/2.784 SF
3 x 9	5.68 (PCs/SF)	18 Pieces/3.168 SF
3 x 12	4.27 (PCs/SF)	12 Pieces/2.808 SF
Falling Water	0.99 (SF/ Sheet)	5 Sheets/4.95 SF
Flat Bar (½ x 5 ¾")		100 Pieces/Box

Shade Variation	Grout Joint Recommendation
V1 - V2 Slight Variation	1/8" (3 mm)

Standards Methods Breaking Strength ASTM C-648 >650 PSI Water Absorption ASTM C-373 Impervious < 0.01% Chemical Resistance ASTM C-650 Unaffected Freeze/Thaw ASTM C-1026 Unaffected

NOTES

Since variations are common in artistic glass tile, we recommend final selection be made from an actual tile mock-up. To achieve optimal results in shading, layout and design, tile should be randomly selected from multiple boxes during installation. We recommend a minimum of 10% overage on all orders. On dimensional patterns, using a grout bag is the best method to target competent and successful grout application. Grout floats should not be used due to the luster glaze. please take care when grouting and protect surface from abrasion. Installation constitutes acceptance. We advise retaining control samples to aid in color matching if additional material is required (match not guaranteed).

MAINTENANCE

A routine cleaning of **Tomei** tile can be done with a light duty non-abrasive, close to neutral pH detergent cleaner.

- * Acceptable for use near open flame or heat source; However it is NOT considered 'Fire Glass'.
- ** All Tomei series tiles are not suitable for usage in pools, spas, or water features.
- ▲ Size and Pattern Limitations: 3 x 6", 3 x 9", 3 x 12" and Falling Water pattern are NOT recommended for use on floors.

FLOOR APPLICATION DEFINITIONS:

Thermal Shock

Light Residential - Flooring areas subject to soft-soled footwear or normal footwear traffic without abrasive soil/dirt, such as bathrooms and bedrooms without exterior access and minimal pivot points.

Residential - Flooring areas subject to soft-soled or normal footwear traffic that may contain amounts of abrasive soil/dirt, such as living rooms, dining rooms or other rooms with exterior access.