## **Tozen Glow**

Dreamy and reflective, Tozen Glow amplifies the handcrafted beauty of the Tozen series by fusing silver or gold leaf for an extra dimension of metallic shimmer beneath the watercolor-like flow of translucent and colored glass.





Please visit LunadaBayTile.com for our complete product offerings, applications and installation instructions.

© 2020 Lunada Bay Tile. All Rights Reserved

RECOMMENDED USAGE				FLOOR APPLICATIONS					
Application			Suitable			Interior		Exterior	
Interior Wall/Backsplash			Yes	Shower		No		No	
Fireplace/Cooktop Surround			Yes *	Steam Shower		No		N/A	
Shower Wall			Yes	Light Residential		Yes		No	
Steam Shower			No	Residential		No		No	
Exterior Wall			No	Note: Silk finish is recommended for floor/foot traffic applications and					
Pool, Spa or Water Feature (fully submerged)			No	usage.					
PRODUCT SPECS				TESTING					
Size (Dimension In Nominal Size)	Coverage (SF Per Sheet)	Coverage Packaging (SF Per Sheet) (Per Box)			Standards Methods				
½ x 1 Mini Brick	1.09	Į	5 Sheets/5.45 SF	Breaking Strength	/	ASTM C-648		>350 PSI	
½ x 4 Brick	0.84	Ę	5 Sheets/4.20 SF	Water Absorption		ASTM C-373	Im	npervious < 0.05%	
Martini (5% x 2")	1.04	Ę	5 Sheets/5.20 SF	Chemical Resistance	1	ASTM C-650		Unaffected	
Shade Variation	Grout Joint Re	ecom	nmendation	Freeze/Thaw	A	ASTM C-1026		Unaffected	
V4 - Random Variation	1/16" (1.6 mr		n)	Thermal Shock ASTM C-		ASTM C-484		Passed	
				Since variations are common in artistic glass tile, we recommend final selection be made from an actual tile mock-up. To achieve optimal results in shading, layout and design, tile should be randomly selected from multiple boxes during installation. We recommend a minimum of 10% overage on all orders. On dimensional patterns, using a grout bag is the best method to target competent and successful grout application. Grout floats should not be used due to the luster glaze. please take care when grouting and protect surface from abrasion. <b>Installation constitutes acceptance</b> . We advise retaining control samples to aid in color matching if additional material is required (match not guaranteed). <b>MAINTENANCE</b> A routine cleaning of <b>Tozen Glow</b> tile can be done with a light duty non-abrasive, close to neutral pH detergent cleaner.					
* Acceptable for use near open flame or heat source; However it is NOT considered 'Fire Glass'.				FLOOR APPLICATION DEFINITIONS:         Light Residential - Flooring areas subject to soft-soled footwear or normal footwear traffic without abrasive soil/dirt, such as bathrooms and bedrooms without exterior access and minimal pivot points.         Residential - Flooring areas subject to soft-soled or normal footwear traffic that may contain amounts of abrasive soil/dirt, such as living rooms, dining rooms or other rooms with exterior access.					